





PRODUCT DATASHEET Bi Metal Standard Tek (Unwashered)

PRODUCT DETAILS

Purpose:	Fastening in aluminium sheeting and panels
Head style:	Hexagonal Drive bit: 5/16" hexagonal
Thread Form:	Twin, coarse thread (Tek 3)/fine thread (Tek 5)
Shank material:	Stainless steel
Material Grade:	AISI A304
Coating:	Electroplated zinc
Recommended drill speed:	1500 - 2500 RPM
Drilling Point Material Grade:	SAE C1022

TEK 3 RANGE UNWASHERED – FOR LIGHT STEEL

Product Code	Size	Drill Point	Effective Thread Length	Drilling Capacity	Steel Thickness
BMHH5.5-25-3	5.5x25mm	Tek 3	14.0mm	1.2-3.5mm	1.2-3.5mm
BMHH5.5-38-3	5.5x38mm	Tek 3	27.0mm	1.2-3.5mm	1.2-3.5mm
BMHH5.5-50-3	5.5x50mm	Tek 3	38.0mm	1.2-3.5mm	1.2-3.5mm
BMHH5.5-65-3	5.5x65mm	Tek 3	55.0mm	1.2-3.5mm	1.2-3.5mm
BMHH5.5-80-3	5.5x80mm	Tek 3	68.0mm	1.2-3.5mm	1.2-3.5mm
BMHH5.5-100-3	5.5x100mm	Tek 3	88.0mm	1.2-3.5mm	1.2-3.5mm

TEK 5 RANGE UNWASHERED – FOR HEAVY STEEL

Product Code	Size	Drill Point	Effective Thread Length	Drilling Capacity	Steel Thickness
BMHH5.5-38-5	5.5x38mm	Tek 5	15.0mm	4.0-12.5mm	4.0-12.5mm
BMHH5.5-50-5	5.5x50mm	Tek 5	30.0mm	4.0-12.5mm	4.0-12.5mm
BMHH5.5-75-5	5.5x75mm	Tek 5	60.0mm	4.0-12.5mm	4.0-12.5mm
BMHH5.5-100-5	5.5x100mm	Tek 5	80.0mm	4.0-12.5mm	4.0-12.5mm

TECHNICAL DATA

Tek 3 range – unfactored pull out values								
		Steel Thickness						
Diameter	Drill Point	1.2mm	1.6mm	2.0mm	2.5mm	3.0mm	4.0mm	
5.5mm	Tek 3	1.7kN	2.1kN	2.5kN	3.2kN	4.3kN	5.5kN	
Tek 5 range – unfactored pull out values								
		тек эт	ange – uniacio	red pull out val	lues			
		тек эт	ange – umacio	•	hickness			
Diameter	Drill Point	4.0mm	5.0mm	•		10.0mm	12.5mm	
Diameter 5.5mm	Drill Point Tek 5			Steel T	hickness	10.0mm 12.0kN	12.5mm 12.4kN	

ULTIMATE MECHANICAL PERFORMANCE			PULLOVER PERFORMANCE			
Diameter	Tensile Strength	Shear Strength	Diameter	In 0.6mm steel	In 1.2mm steel	
5.5mm	10.6kN	6.7kN	5.5mm	2.7kN	8.4kN	

NOTE: The results expressed in this document are determined from empirical testing. Specifiers, end-users and other third parties should make their own decision(s) on what safety factors to use relevant to their design(s)/ application(s). This document is provided, strictly: without prejudice, without recourse, without liability, non-assumpsit, no assured value, errors and omis-