

# PRODUCT DATASHEET

## Bi Metal Standard Tek (Washed)



### Product Details

<b>Purpose:</b>	Fastening in aluminium sheeting and panels
<b>Head style:</b>	Hexagonal Drive bit: 5/16" hexagonal
<b>Thread Form:</b>	Coarse thread (Tek 3)/Fine thread (Tek 5)
<b>Coating:</b>	Electroplated Zinc $\geq 5\mu\text{m}$
<b>Shank Material:</b>	Stainless Steel
<b>Shank Material Grade:</b>	EN 1.4301/ A2 (AISI 304)
<b>Washer:</b>	16mm $\varnothing$ bonded EPDM
<b>Washer Steel Material Grade:</b>	EN 1.4301/ A2 (AISI 304)
<b>Drill Point Material:</b>	Carbon Steel
<b>Drill Point Material Grade:</b>	SAE C1022
<b>Recommended Drill Speed:</b>	1,500 - 2,500 RPM

### Bi-Metal Standard TEK (Washed)- Products for use in Light Gauge Steel Applications (1.2mm to 4.0mm mild steel)

SKU	Nominal Dimensions, $d_{\text{nom}} \times L_{\text{nom}}$ (mm)	Effective Thread Length $L_{\text{thread}}$ (mm)	Drill Point	Drilling Capacity $H_{\text{cap}}$ (mm)
BMBW5.5-25-3	5.5 x 25.0	Fully Threaded	TEK 3	1.2 - 4.0
BMBW5.5-32-3	5.5 x 32.0	Fully Threaded		
BMBW5.5-38-3	5.5 x 38.0	Fully Threaded		
BMBW5.5-50-3	5.5 x 50.0	Fully Threaded		
BMBW5.5-75-3	5.5 x 75.0	60mm		
BMBW5.5-100-3	5.5 x 100.0	75mm		

### Bi-Metal Standard TEK (Washed)- Products for use in Heavy Gauge Steel Applications (4.0mm to 12.0mm mild steel)

SKU	Nominal Dimensions, $d_{\text{nom}} \times L_{\text{nom}}$ (mm)	Effective Thread Length $L_{\text{thread}}$ (mm)	Drill Point	Drilling Capacity $H_{\text{cap}}$ (mm)
BMBW5.5-38-5	5.5 x 38.0	Fully Threaded	TEK 5	4.0 - 12.0
BMBW5.5-50-5	5.5 x 50.0	Fully Threaded		
BMBW5.5-65-5	5.5 x 65.0	Fully Threaded		
BMBW5.5-75-5	5.5 x 75.0	Fully Threaded		
BMBW5.5-100-5	5.5 x 100.0	Fully Threaded		

### Ultimate Withdrawal Resistance, $N_{Rk}$ , from S355JR Steel (N)

Diameter	Drill Point	Nominal Substrate Thickness, $t_{\text{nom}}$				
		1.0mm	1.5mm	2.0mm	3.0mm	4.0mm
5.5	TEK 3	1.1 kN	2.4 kN	3.5 kN	6.7 kN	9.7 kN

### Ultimate Withdrawal Resistance, $N_{Rk}$ , from S355JR Steel (N)

Diameter	Drill Point	Nominal Substrate Thickness, $t_{\text{nom}}$					
		4.0mm	5.0mm	6.0mm	8.0mm	10.0mm	12.5mm
5.5	TEK 5	6.5 kN	7.8 kN	10.0 kN	11.5 kN	12.0 kN	12.4 kN

### Ultimate Mechanical Performance

Property	Magnitude
Tensile Capacity, $(F_{\text{ult}}, R_k)$	14.4 kN
Shear Capacity, $(V_{\text{ult}}, R_k)$	10.8 kN

### Ultimate Pullover Performance

Nominal steel Thickness, $t_{\text{nom}}$	Magnitude
0.6mm	2,700 N
1.2mm	8,400N

determined from empirical testing. Specifiers, end-users and other third parties should make their own decision(s) on what safety factors to use relevant to their design(s)/ application(s). This document is provided, strictly: without prejudice, without recourse, without liability, non-assumpsit, no assured value, errors and omissions excepted, subject to change without notice and all rights reserved.  
©Evolution Fasteners UK Ltd, 2021.